




HOSPITALITY



OFFICE

waterPLUS
BEVERAGE INNOVATIONS

Fontemagna Compact 150L



150
lt/h

stainless
STEEL

GAS
R290

ENERGY
SAVING

PORTION
CONTROL

ALUMINIUM

FIZZ

TOUCH
SCREEN

NSF.

AMBIENT

ICE
BANK


COLD

BevPlus (PTY) LTD.

13 Michigan Street, Airport Industria, Cape Town, 7490, South Africa

www.bevplus.com | +27 (0)21 820 9500 | info@bevplus.com

TECHNICAL SPECIFICATIONS

Fontemagna Compact 150L FIZZ	
Cooling capacity (l/h)	150
Max continuous supply (l)	80
Cold water temperature*	5 - 12 °C
Pump	Professional rotary carbonation pump
Cooling technology	Ice bank - double coil in stainless steel
Ice bank capacity (l)	18
Ice bank (kg)	8
Condensation	Forced ventilation
Refrigerant gas	R290
Adjustable thermostat	Yes
Supply	230 V - 50 Hz
Compressor power	1/3 HP
Absorbed power	920 W - 4 A
Working room temperature	Min 16°C - Max 32°C
Inlet water pipe	Ø5/16" (8 mm)
Inlet CO ₂ pipe	Ø5/16" (8 mm)
Dispensing area height (mm)	310
Typology	Countertop
Net weight (kg)	45
Gross weight (kg)	60
Dimensions W x D x H (mm)	455 x 600 x 512
Packaging dimensions (mm)	550 x 700 x 750
Dispensing options	Cold still, cold sparkling and room temperature water
Materials	Stainless steel and aluminum parts
Push buttons	Electronic touch screen board
Alarms	No water, no CO ₂ , leakage
OTHER CHARACTERISTICS	
Energy saving device. Safety inlet valve Anti-splash drip tray. Water pressure reducer included. Predisposition for fixing activated carbpn filter (OPTIONAL) onside the machine	
CERTIFICATIONS	
     	

BevPlus (PTY) LTD.

13 Michigan Street, Airport Industria, Cape Town, 7490, South Africa

www.bevplus.com | +27 (0)21 820 9500 | info@bevplus.com